



PIJPBEUGEL RVS A2 – SCHROEFSLUITING

Ø 12 – 14 tot 210 – 212 mm

125

RVS A2 1.4301

Met rubber inlage DIN 4109

M8 – M8/M10 – M10

info
125

www.hazal.nl

offerte
125

verkoop@hazal.nl

- tussentijdse model wijzigingen voorbehouden -

Pallet	Verpakt per	Artikel nr.	Afmeting	Bereik (mm)	Inch	Moer	Materiaal	Max. Load
20250	150	125.02.0012	12 mm	12 – 14	1/4"	M8	1,50 x 18	2,0 kN
20250	150	125.02.0015	15 mm	15 – 19	3/8"	M8	1,50 x 18	2,0 kN
13500	100	125.02.0021	20 mm	21 – 23	1/2"	M8	1,50 x 18	2,0 kN
10500	100	125.02.0026	25 mm	26 – 28	3/4"	M8	1,50 x 18	2,0 kN
10125	75	125.02.0032	32 mm	32 – 35	1"	M8	1,50 x 18	2,0 kN
6750	50	125.02.0040	40 mm	40 – 43	1 1/4"	M8	1,50 x 18	2,0 kN
5250	50	125.02.0044	44 mm	44 – 49	1 1/2"	M8	1,50 x 18	2,0 kN
3750	50	125.02.0050	50 mm	50 – 56		M10/M8	2,00 x 18	2,5 kN
3750	50	125.02.0057	57 mm	57 – 61	2"	M10/M8	2,00 x 18	2,5 kN
3000	50	125.02.0063	63 mm	63 – 67		M10/M8	2,00 x 18	2,5 kN
3000	50	125.02.0070	70 mm	70 – 73		M10/M8	2,00 x 18	2,5 kN
3000	50	125.02.0074	74 mm	74 – 80	2 1/2"	M10/M8	2,00 x 18	2,5 kN
3000	50	125.02.0083	83 mm	83 – 91	3"	M10/M8	2,00 x 18	2,5 kN
1800	25	125.02.0101	101 mm	101 – 106		M10/M8	2,50 x 23	3,0 kN
1800	25	125.02.0108	108 mm	108 – 114	4"	M10/M8	2,50 x 23	3,0 kN
1800	25	125.02.0115	115 mm	115 – 116		M10/M8	2,50 x 23	3,0 kN
600	25	125.02.0125	125 mm	125		M10/M8	2,50 x 23	3,0 kN
600	25	125.02.0131	131 mm	131 – 135	5"	M10	2,50 x 23	3,0 kN
600	25	125.02.0137	137 mm	137 – 142		M10	2,50 x 23	3,0 kN
480	20	125.02.0159	159 mm	159 – 163		M10	2,50 x 23	3,0 kN
480	20	125.02.0165	165 mm	165 – 169	6"	M10	2,50 x 23	3,0 kN
360	15	125.02.0200	200 mm	200 – 206		M10	2,50 x 23	3,0 kN
240	10	125.02.0210	210 mm	210 – 212		M10	2,50 x 23	3,0 kN

Materiaal		RVS A2 1.4301
Rubber inlage	DIN 4109	Dikte 4 mm Temperatuur -40° tot +100° C
Tot Ø 125 mm		Schroeven M6 DIN 7985 met anti-verliesringen
Vanaf Ø 131-135 mm		Schroeven M8 DIN 933 + moer DIN 934 A2 1.4301
Aansluitmoer	M8 x 8 mm	M8/M10 x 15 mm M10 x 10 mm A2 1.4301
Aanbevolen maximum load	–	Zie tabel

