



PIJPBEUGEL RVS-304 – SCHROEFSLUITING

Ø 15 – 19 tot 210 – 212 mm

126

info www.hazal.nl offerte verkoop@hazal.nl
126 126

RVS-304 / A2 1.4301

(zonder inlage)

- tussentijdse model wijzigingen voorbehouden -

M8 – M8/M10 – M10

Ø

Verpakt per	Artikel nr.	Afmeting	Bereik (mm)	Inch	Moer	Materiaal	Max. Load
50	126.02.0015	15 mm	15 – 19	3/8"	M8	1,50 x 18	2,0 kN
50	126.02.0021	20 mm	21 – 23	1/2"	M8	1,50 x 18	2,0 kN
50	126.02.0026	25 mm	26 – 28	3/4"	M8	1,50 x 18	2,0 kN
50	126.02.0032	32 mm	32 – 35	1"	M8	1,50 x 18	2,0 kN
50	126.02.0040	40 mm	40 – 43	1 1/4"	M8	1,50 x 18	2,0 kN
50	126.02.0044	44 mm	44 – 49	1 1/2"	M8	1,50 x 18	2,0 kN
50	126.02.0050	50 mm	50 – 56		M10/M8	2,00 x 18	2,5 kN
50	126.02.0057	57 mm	57 – 61	2"	M10/M8	2,00 x 18	2,5 kN
50	126.02.0063	63 mm	63 – 67		M10/M8	2,00 x 18	2,5 kN
50	126.02.0070	70 mm	70 – 73		M10/M8	2,00 x 18	2,5 kN
50	126.02.0074	74 mm	74 – 80	2 1/2"	M10/M8	2,00 x 18	2,5 kN
50	126.02.0083	83 mm	83 – 91	3"	M10/M8	2,00 x 18	2,5 kN
25	126.02.0101	101 mm	101 – 106		M10/M8	2,50 x 23	3,0 kN
25	126.02.0108	108 mm	108 – 114	4"	M10/M8	2,50 x 23	3,0 kN
25	126.02.0115	115 mm	115 – 116		M10/M8	2,50 x 23	3,0 kN
25	126.02.0125	125 mm	125		M10/M8	2,50 x 23	3,0 kN
25	126.02.0131	131 mm	131 – 135	5"	M10	2,50 x 23	3,0 kN
25	126.02.0137	137 mm	137 – 142		M10	2,50 x 23	3,0 kN
20	126.02.0159	159 mm	159 – 163		M10	2,50 x 23	3,0 kN
20	126.02.0165	165 mm	165 – 169	6"	M10	2,50 x 23	3,0 kN
15	126.02.0200	200 mm	200 – 206		M10	2,50 x 23	3,0 kN
10	126.02.0210	210 mm	210 – 212		M10	2,50 x 23	3,0 kN

Materiaal RVS-304 / A2 1.4301
Tot Ø 125 mm Schroeven M6 DIN 7985 met anti-verliesringen
Vanaf Ø 131-135 mm Schroeven M8 DIN 933 + moer DIN 934 A2 1.4301
Aansluitmoer M8 x 8 mm M8/M10 x 15 mm M10 x 10 mm RVS-304 / A2 1.4301
Aanbevolen maximum load – Zie tabel

